

# DH-TPC-BF3221-T

## Thermal Temperature Monitoring Camera



- 256 x 192 VOx uncooled thermal sensor technology
- Athermalized Lens (thermal camera), Focus-free
- Smart linkage with strobe light & audio
- Measurement Accuracy:  $\pm 0.3^{\circ}\text{C}$ , with black body
- Temperature Measurement Range:  $30^{\circ}\text{C}$  to  $45^{\circ}\text{C}$
- Micro SD memory, IP67, ePoE, PoE

### System Overview

Dahua thermal cameras characterized by non-contact, rapid, and no risk to temperature testers, etc. It can be conveniently deployed in public places with dense crowds, and can be used for efficient and safe preliminary screening of temperature anomalies.

### Technical Specification

#### Thermal Camera

Effective Pixels	256(H)x192(V)
Pixel Size	12 $\mu\text{m}$
Thermal Sensitivity (NETD)	<50mK@f/1.1
Spectral Range	8 $\mu\text{m}$ –14 $\mu\text{m}$
Image Setting	Brightness/Sharpness/ROI/AGC/FFC/3D DNR
Color Palettes	18(Whitehot/Blackhot/Ironrow/Icefire/Fusion/Rainbow/Globow/Iconbow1/Iconbow2 .etc)
Lens Type	Fixed
Focus Control	Athermalized, Focus-free
Focal Length	7.1mm
Angle of View	H: 24° V: 18°

#### Visible Camera

Image Sensor	1/2.8" 2M CMOS
Effective Pixels	1920(H)x1080(V)
Electronic Shutter Speed	1/1 ~ 1/30,000s
Min. Illumination	Color: 0.005Lux; B/W: 0.0005Lux; 0Lux (IR on)
IR Distance	35m

IR On/Off Control	Auto/Manual
IR LEDs	1
Focal Length	8mm
Aperture	F1.9
Angle of View	H: 40° V: 22°
BLC	Yes
WDR	Yes
HLC	Yes
White Balance	Auto/Manual/Indoor/Outdoor/Tracking/Sodium lamp/Street lamp/Natural
AGC	Auto; Manual

#### Temperature Measurement

Measurement Range	$30^{\circ}\text{C}$ ~ $+45^{\circ}\text{C}$
Measurement Accuracy	$\pm 0.3^{\circ}\text{C}$ , with black body

## Video

Compression	H.265/H.264/MJPEG
Frame Rate	<p>Thermal Main stream: (1280 × 1024/1024 × 768/640 × 480/256 × 192@), 1280 × 960 by default; Sub stream: (640 × 512/256 × 192@), 256 × 192 by default</p> <p>Visible Main stream: (1920 × 1080/1280 × 720/704 × 576@), 1920 × 1080 by default; Sub stream: (704 × 576/352 × 288@), 355 × 288 by default</p> <p>Thermal: 50Hz: Main stream (1fps-25fps),25fps by default; sub stream (1fps-25fps),15fps by default; 60Hz: Main stream (1fps-30fps),30fps by default; sub stream (1fps-30fps),15fps by default;</p> <p>Visual: 50Hz: Main stream (1fps-25fps),25fps by default; sub stream (1fps-25fps),15fps by default; 60Hz: Main stream (1fps-30fps),30fps by default; sub stream (1fps-30fps),15fps by default;</p>

## Audio

Compression	G.711a/G.711Mu/AAC
-------------	--------------------

## Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
Interoperability	Profile S & G, API
Streaming Method	Unicast/Multicast
Max. User Access	10 Users/20 Users

## Certifications

Certification	CE FCC
---------------	--------

## Interface

Audio Interface	1/1 In/Out
RS485	Support
Alarm	2/1 In/Out

## Electrical

Power Supply	12V±20% DC, 1.2A, PoE (802.3af), ePoE
Power Consumption	Basic: 5.0W Maximum: 12W (power adapter excluded)

## Environmental

Operating Condition	10°C ~ +30°C
Operating Humidity	≤95%
Ingress Protection	IP67

## Construction

Casing	Metal
Dimensions	279.9mm × 103.8mm × 95.8mm(With bracket)
Weight	< 1.4Kg

## Ordering Information

Type	Part Number	Description
DH-TPC-BF3221-T	DH-TPC-BF3221P-TB7F8 DH-TPC-BF3221N-TB7F8	Thermal: 256x192 7mm lens Visible: 2MP 8mm lens

## Dimensions (mm)

